



**DEMAND THE BEST.
MARITIME™ TEAK DECK CAULK
MADE FOR THE TOUGHEST CONDITIONS.**

Developed by teak deck pros for teak deck pros. Bonds to teak with uncompromising adhesion for a long-lasting, flexible, waterproof seal. Requires no primer. Saves labor, time, and money. Proven over years of trouble-free use in all climate conditions.

To find out more, call toll-free (800) 274-8325
or visit us on the web at www.maritimewoodproducts.com



MARITIME™
TEAK DECK CAULK
The Professional's Favorite.

MARITIME™ Teak Deck Caulk

is absolutely the best caulk on the market for teak and other maritime woods.

Requires No Primer

Our technologically advanced product achieves exceptional adhesion without the need for a primer, totally eliminating the extra labor and chemical cost of priming. MARITIME Teak Deck Caulk is a one-part, neutral curing, silicone adhesive sealant that is specially formulated for teak and other maritime woods.

It cures when exposed to moisture in the air to form a tough, flexible, solid rubber seal. The cured caulk provides excellent temperature stability and resistance to chemicals and ultra violet rays. It is non-corrosive to all substrates and sandable when cured.

“As a builder of teak decks, we work with deck caulk all day, every day. Dissatisfaction with existing deck caulks led us to develop our own solution. It had to be really good and it had to be easy to use. Maritime Teak Deck Caulk is the key component of our beautiful, long-lasting teak decks.”

Michael Viener
President, Maritime Wood Products

Easy to Use

MARITIME Teak Deck Caulk has a firm paste-like consistency that guns and tools with ease. Our special manufacturing process removes virtually all air from the caulk to eliminate voids and bubbles. The caulk will stick to any properly prepared surface, and to itself, simplifying any application.

Fast Curing

MARITIME Teak Deck Caulk skins over and cures rapidly. It forms a tack-free skin in 15-20 minutes. A freshly caulked deck is safe to walk on the next day and can be sanded within 24-48 hours of application (longer where temperature and humidity are low). Full cure and maximum adhesion is achieved in approximately 14 days.





The Professional's Caulk

MARITIME Teak Deck Caulk is fast becoming the favorite caulk of teak deck pros, builders, and repair yards. Whether caulking teak or another maritime wood, you won't find a product that is more reliable, faster, and easier to use.

Why teak deck pros, builders, and repair yards use MARITIME Teak Deck Caulk:

✓ **Primerless Application:** Requires no primer, saves time, eliminates extra labor, and chemical cost.

✓ **Easy to Use:** Has a firm paste-like consistency that guns and tools easily. Will stick to any properly prepared surface, and to itself, simplifying the application process.

✓ **Fast Curing:** Forms a tack-free skin in 15-20 minutes. A freshly caulked deck is safe to walk on the next day.

✓ **Smooth Sanding:** Formulated for smooth and easy sanding.

✓ **Bulldog Adhesion:** Bonds to teak with uncompromising adhesion for a long-lasting, flexible, waterproof seal.

✓ **Exceptional Durability:** Proven over years of trouble-free use in all climate conditions, including the tropics. Cured caulk has excellent temperature stability and resistance to chemicals and ultra violet rays.

***Developed by teak deck pros
for teak deck pros.***

Caulk Quantity Estimator:

Linear feet of seam per 10.3 oz. cartridge
(allowing for 10% waste):

Seam Depth	Seam Width	Seam Width	Seam Width
	1/8"	3/16"	1/4"
1/4"	32	24	16
3/8"	24	16	12
1/2"	16	12	8
5/8"	–	9	6
3/4"	–	6	4
1"	–	3	2



MARITIME™

TEAK DECK CAULK

The Professional's Favorite.

MARITIME™

TEAK DECK CAULK

Product Description:

A specially formulated one-part, neutral curing, silicone adhesive sealant.

Typical Properties:

Uncured Physical Properties

Specific Gravity	1.30
Viscosity	Thixotropic Paste
Cure Time at 75° F (24° C) and 50% RH (3/8" thickness)	24 hours
Extrusion Rate	250g/minute
Tack-Free Time	15-20 minutes

Cured Physical Properties

Elongation	400
Durometer, Shore A Hardness, Points	35
Tensile Strength, psi	300

Color

Black. Also available in white and other custom colors, subject to minimum order quantities.

Specifications:

Product meets or exceeds the requirements of Federal Specifications TT-S-00230C, TT-S-001543A, and ASTM C920-02. Manufactured in compliance with ISO 9001/2000.

Application:

Use at ambient temperatures between 40°– 90° F (5° – 32° C).

Storage:

Store in original, un-opened container at or below 80° F (27° C).

Shelf Life:

Product has a shelf life of 12 months from the date of manufacture. Packaging is marked with recommended "use by" date.

Packaging:

MARITIME Teak Deck Caulk is supplied in the following sizes:

MWP-DC10	10.3 fl.oz. (305ml) cartridge	12 cartridges per case
MWP-DC20	20.0 fl.oz. (592ml) sausage	16 sausages per case
MWP-DC576	4.5 gallon (17.03 liter) pail	–

For more information about MARITIME Teak Deck Caulk, including a Materials Safety Data Sheet (MSDS), please contact us directly at the numbers listed below or you may contact your local distributor.

Maritime Wood Products Corp.

3361 S.E. Slater Street
Stuart, Florida 34997

Website: www.maritimewoodproducts.com

Toll-Free: (800) 274-8325

Telephone: (772) 287-2919

Fax: (772) 287-5031

E-mail: sales@maritimewoodproducts.com



MARITIME™
TEAK DECK CAULK
The Professional's Favorite.